

Ex Cable glands

- Plastic versions



Type: Polyamide Ex
acc. DIN EN 50014/19/20;

Certification: II G/D

Ingress protection: IP 68 with seal

Temperature range: -20°C to +80°C

Material: Polyamide 6

Colour: black (RAL 9005)
or blue (RAL 5012)

Types with other temperature ranges on request

Type	Cable Ø	SW	Crossc. dim.	VPE	Order No.	Order No.
PG					black	blue
7	3,5 - 6	15	16,8	20	08.06 00 07	08.06 50 07
9	5 - 8	19	21,3	20	08.06 00 09	08.06 50 09
11	6 - 10	22	24,2	20	08.06 00 11	08.06 50 11
13,5	8 - 13	24	26,8	20	08.06 00 13	08.06 50 13
16	10 - 15	26	29,2	20	08.06 00 16	08.06 50 16
21	13 - 19	32	35,3	20	08.06 00 21	08.06 50 21
29	17 - 25	41	45,2	10	08.06 00 29	08.06 50 29
36	24 - 32	52	57,6	10	08.06 00 36	08.06 50 36
42	28 - 38	59	65,1	10	08.06 00 42	08.06 50 42
48	34 - 44	65	71,25	10	08.06 00 48	08.06 50 48
Metric						
M 16 x 1,5	5 - 8	19	21,3	20	08.08 06 16	08.08 07 16
M 20 x 1,5	8 - 13	24	26,7	20	08.08 06 20	08.08 07 20
M 25 x 1,5	13 - 19	32	35,0	20	08.08 06 25	08.08 07 25
M 32 x 1,5	17 - 25	41	45,3	10	08.08 06 32	08.08 07 32
M 40 x 1,5	24 - 32	52	57,2	10	08.08 06 40	08.08 07 40
M 50 x 1,5	28 - 38	59	65,3	10	08.08 06 50	08.08 07 50
M 63 x 1,5	34 - 44	65	71,3	10	08.08 06 63	08.08 07 63



Type: Ex blind plug plastic
acc. DIN EN 50014/19/20;

Certification: II G/D

Ingress protection: IP 68 with seal

Temperature range: -20°C to +80°C

Material: Polyamide 6

Colour: black (RAL 9005)

Types with other temperature ranges on request


Type	Cable Ø	SW	Crossc. dim.	VPE	Order No.	Order No.
PG					black	blue
7		15	16,5	100	08.05 67 07	
9		19	20,9	100	08.05 67 09	
11		22	24,2	100	08.05 67 11	
13,5		24	26,4	100	08.05 67 13	
16		27	29,7	100	08.05 67 16	
21		32	35,2	100	08.05 67 21	on request
29		40	44	50	08.05 67 29	
36		54	59,4	20	08.05 67 36	
42		59	64,9	20	08.05 67 42	
48		64	70,4	20	08.05 67 48	
Metric						
M 16 x 1,5		19	21,3	100	08.09 06 16	
M 20 x 1,5		23	25,3	100	08.09 06 20	
M 25 x 1,5		28	30,8	100	08.09 06 25	
M 32 x 1,5		36	39,3	100	08.09 06 32	on request
M 40 x 1,5		44	48,3	20	08.09 06 40	
M 50 x 1,5		54	59,7	20	08.09 06 50	
M 63 x 1,5		67	74,0	20	08.09 06 63	

Ex Cable glands

- Brass versions



Type: Cable gland brass
nickel-plated, incl seal

Certification:  II 2G/D

Ingress protection: IP 68

Temperature range: -20°C to +130°C

Types with other temperature ranges on request

Type	Cable Ø	SW	Crossc. dim.	VPE	Order No.
PG					
7	3,5 - 6	14	15,55	24	08.04 07 07
9	4 - 8	17	19,1	24	08.04 07 09
11	6 - 10	20	22,3	24	08.04 07 11
13,5	6 - 12	22	24,9	24	08.04 07 13
16	10 - 14	24	26,65	24	08.04 07 16
21	14 - 18	30	33,65	24	08.04 07 21
29	20 - 25	40	44,0	12	08.04 07 29
36	22 - 32	50	55,0	12	08.04 07 36
42	32 - 38	57	59,9	12	08.04 07 42
48	37 - 44	64	69,9	12	08.04 07 48
Metric					
M 12 x 1,5	3 - 6,5	14	15,55	50	08.08 08 12
M 16 x 1,5	4 - 8	17	19,11	10	08.08 08 16
M 20 x 1,5	6 - 12	22	24,4	10	08.08 08 20
M 25 x 1,5	14 - 18	30	33,65	10	08.08 08 25
M 32 x 1,5	20 - 25	40	44	10	08.08 08 32
M 40 x 1,5	22 - 32	50	55	5	08.08 08 40
M 50 x 1,5	32 - 38	57	59,9	1	08.08 08 50
M 63 x 1,5	37 - 44	64/68	69,9/74,27	1	08.08 08 63

Ex Cable glands

- Stainless steel versions



Type: Cable gland stainless steel, 1.4305

Certification:  II 2G/D

Ingress protection: IP 68

Temperature range: -20°C to +95°C

Types with other temperature ranges on request

Type	Cable Ø	SW	Crossc. dim.	VPE	Order No.
PG					
7	3 - 6,5	14	15,6	24	08.04 08 07
9	4 - 8	17	19,0	24	08.04 08 09
11	5 - 10	22	24,4	24	08.04 08 11
13,5	6 - 12	22	24,4	12	08.04 08 13
16	10 - 14	24	26,45	12	08.04 08 16
21	13 - 18	30	33,5	12	08.04 08 21
29	18 - 25	41	45,1	12	08.04 08 29
36	22 - 32	50	55,0	12	08.04 08 36
Metric					
M 12 x 1,5	3 - 6,5	14	15,6	10	08.04 02 12
M 16 x 1,5	5 - 10	20	24,4	10	08.04 02 16
M 20 x 1,5	9 - 14	24	26,45	10	08.04 02 20
M 25 x 1,5	13 - 18	30	33,4	10	08.04 02 25
M 32 x 1,5	17 - 25	41	45,0	10	08.04 02 32
M 40 x 1,5	24 - 33	50	55,0	5	08.04 02 40


Ex Cable glands

- Breather drain plugs



Type	VPE	Order No.
Metric		
M 25 x 1,5	1	08.51 01 25

Type: Breather drain plug

Certification:  II 2G/D

Ingress protection: IP 66

Material: Polyamide

Temperature: -20°C to +40°C



Type	VPE	Order No.
Metric		
M 20 x 1,5	1	08.51 10 20

Type: Breather drain plug
stainless steel

Certification:  II 2 G/D

Material: 1.4305

Sealing inset: NBR

Ingress protection: IP 66

Temperature range: -20°C to +40°C

Other types with other temperature ranges on request